

sMRT AU10-M

The sMRT AU10-M is a DSC Class M Maritime Survivor Locating Device (MSLD). Once armed, the device is designed to activate automatically in the event of a man overboard incident. Following activation, the sMRT AU10-M transmits a 121.5 MHz and VHF DSC distress alert whilst continuously updating location information, via AIS. Automatic activation will alert you of every MOB incident within 2 - 5 seconds.

121.5
MHz

121.5 MHz

A low power homing signal to assist local rescue efforts

VHF
DSC

VHF DSC

All nearby vessels are automatically alerted of the man overboard situation via DSC

AIS

AIS

The live location of the man overboard is regularly updated and displayed via AIS

DUAL
GNSS

Dual GNSS

Combines both GPS & Galileo GNSS receivers for accelerated detection

M
Class-M

Class-M

Compliant to European regulation ECC/DEC/(22)02 relevant to the usage of MOB devices




PRODUCT FEATURES



STROBE LIGHT

Antenna can be unscrewed and detached for easy storage



WATER SENSOR

AU transmissions will automatically activate in water



MANUAL ACTIVATION

Easy push button allows the PLB to be manually activated



ARMING SWITCH

Arming switch, locks in and clearly displays if the PLB is ON or OFF



Audible Alarm

Highlights activation to aid location and raise awareness of false activation



Test Functionality

Manual device safety, providing a health check on power and functionality



Dual Activation Methods

Device can be activated manually or after immersion in water meaning it will still work if user is incapacitated



Clipping System

Secure clipping system allows easy attachment options for life jackets



Dual GNSS Receivers

GPS and Galileo GNSS receivers for accelerated location detection



Water Proof

Designed to withstand submersion up to 10 meters, ensuring its protection against water damage

WHAT IS A Class-M MAN OVERBOARD DEVICE?

A Class-M MOB (Man Overboard) device is an AIS-enabled device designed to comply with ECC/DEC/(22)02 regulations. From December 31, 2024, only Class-M compliant MOB's and Mobile Aids to Navigation (AtoN) will be allowed to operate on AIS channels 1 and 2 in countries adopting the regulation, ensuring these channels are reserved for emergency use. Non-compliant devices will be restricted to channel 2006, which is not monitored for emergencies.



GENERAL

BATTERY TYPE	6V Li-MnO ₂
BATTERY LIFE	Minimum of 12 hours at -20°C
BATTERY SHELF LIFE AT +20°C	>3 years
OPERATING TEMPERATURE	-20° to +55°C
STORAGE TEMPERATURE	-45° to +70°C
OPERATING HUMIDITY	To 95% non-condensing
SHOCK	20G min
VIBRATIONS	EuroCAE ED-14F
FLAMMABILITY RATING	ED 14F 26.3.3 Category C:
BUOYANCY	Buoyant (index=9%)
TRANSPORTATION	Air cargo UN 3091 not hazardous
DIMENSIONS (CASE)	80mm (H) x 95mm (W) x 35mm (D)
WEIGHT	250g
ENVIRONMENTAL	EN 303 132
STROBE LIGHT	15 Candela
ENVIRONMENTAL RESISTANCE	IP68:10
MOUNTING OPTIONS	Designed to integrate with a SOLAS approved life jacket
SELF ID	ITU-R M.585 compliant factory programmed freeform Maritime Identity with 972 prefix
COMPASS SAFE DISTANCE	30cm (for <1° deflection)
ALERTING RADIUS	Up to 5NM (depending on height of antenna)*

TRANSMITTER PACKAGES

AIR BAND FREQUENCIES	121.500 MHz
AIS Tx POWER OUTPUT	Nominal 1W EIRP
VHF TRANSMISSION FREQUENCIES	VHF DSC Channel 70: 156.525 MHz, AIS Channel 1: 161.975 MHz , AIS Channel 2: 162.025 MHz
VHF DSC Tx POWER OUTPUT	Nominal 1W EIRP
SIGNALLING TYPE	AIS and VHF-DSC
DISTRESS MODULATION	AM compliant to ITU-R M.690-3
AIR BAND POWER	100mW PERP
MARINE-BAND POWER	Nominal 1W EIRP
VHF ANTENNA	Centre-fed dipole, comprising coaxial cable and lambda/8 coil whip

GNSS RECEIVER

GNSS RECEIVER TYPE	GPS plus Galileo
TTFF (TIME TO FIRST FIX)	30 seconds (typical) with nominal GPS signal levels -130dBm
GNSS UPDATE RATE	Every minute

VHF DSC AND AIS ALERTS

AIS	Within 30 seconds of GNSS position acquisition
INITIAL OPEN LOOP DSC ALERT	Within 30 seconds after activation
SUBSEQUENT OPEN LOOP DSC ALERTS	Every 5 minutes for the first 30 minutes, every 10 minutes thereafter until VHF-DSC acknowledgement or the battery expires
FIRST DSC GPS DATA ALERT SENT	Immediately after GNSS position acquired

CONTROLS AND OPERATION

AUTOMATIC WATER ACTIVATION	After 2 seconds of water sensor immersion
MANUAL ACTIVATION	Once armed, press Activation Button
OPERATING TIME	>12 hours continuous
STANDBY BATTERY LIFE	>3 years
PERMANENTLY ARMED	12 hours operation if armed for 12 months
GPS POSITION UPDATE	Minimum of 6 per minute
GPS TIME TO FIRST LOCK	Typically <1 minute under normal operating conditions
ALERT INDICATION	Audible and visible

APPROVALS

EUROPEAN APPROVALS	EN 303 132 V2.1.1
EMC	EN 301 489-22 V1.3.1 EN 301 489-1 V1.8.1
SAFETY	EN 60950-1:2006
MARINE	IEC 60945:2002
RADIO (121.5 MHZ)	EN 300 152-2 V1.1.1 EN 302 961-2 V1.2.2
RADIO (AIS)	ETS 303 098-1 V1.2.1 RTCM 11901.1:2012

* Expected range derived from sea trials. Actual alerting range dependent on sea state, atmospheric conditions and height/altitude of receiving antenna.



Call +1-772-388-1326

Email sos@marinerescuetechnologies.com

Visit www.marinerescuetechnologies.com

1623 US Highway 1, Suite A1, Sebastian, FL, 32958

